




## SPECIALTY. PRESSURE REGULATORS.

SERIES	FEATURES	MAX INLET PRESSURE	FLOW CAPACITY	BODY MATERIAL
<b>4902 SERIES</b> 	<ul style="list-style-type: none"> <li>• Demand flow regulator</li> <li>• Diaphragm Sensed (Buna-n or Viton®)</li> <li>• The unique high flow capability allows multiple analyzers on a single docking station</li> <li>• Integral relief valve</li> <li>• 40 micron stainless steel inlet filter</li> </ul>	3000 psig / 206.82 bar	3.0 lpm @ 3” H <sub>2</sub> O  up to 8 lpm with increased vacuum	6061-T6 Aluminum, Clear Anodized  303 Stainless Steel  SAE 360 Brass, Nickel Plated
<b>4903 SERIES</b> 	<ul style="list-style-type: none"> <li>• Demand flow regulator</li> <li>• Diaphragm Sensed (Buna-n or Viton®)</li> <li>• Compact size (2” diameter)</li> <li>• 40 micron stainless steel inlet filter</li> <li>• Stainless steel body &amp; wetted components provide minimum degradation to cylinder gases.</li> </ul>	3000 psig / 206.82 bar	Permits the flow of gas at less than 3” H <sub>2</sub> O	303 Stainless Steel  6061-T6 Aluminum, Clear Anodize  SAE 360 Brass, Nickel Plated
<b>4050 SERIES</b> 	<ul style="list-style-type: none"> <li>• Two stage</li> <li>• High sensitivity</li> <li>• Adjustable within 0.2 inches H<sub>2</sub>O / 0.007 psig of target pressure on the 0-2 psig control pressure config.</li> <li>• Optional panel mounting nuts</li> </ul>	3000 psig / 206.82 bar	15 lpm	6061-T6 Aluminum, Clear Anodized  Stainless Steel  SAE 360 Brass

*Viton® is a registered trademark of E.I.dePont de Nemours and Company*