









## TRANSPORTABLE. PRESSURE REDUCING REGULATORS.

SERIES	FEATURES	MAX INLET PRESSURE	FLOW CAPACITY	BODY MATERIAL
<b>2300N SERIES</b> 	<ul style="list-style-type: none"> <li>• Single stage</li> <li>• Neoprene or Viton® diaphragm</li> <li>• Neoprene seat</li> <li>• Outlet pressures up to 60 psig / 4.14 bar</li> </ul>	500 psig / 34.5 bar  <i>(dependent upon configuration)</i>	Cv: 0.04	SAE 360 Brass  6061-T6 Aluminum, Clear Anodized
<b>2310C SERIES</b> 	<ul style="list-style-type: none"> <li>• Single stage</li> <li>• Viton® or neoprene diaphragm</li> <li>• PFA Teflon® seat</li> <li>• Outlet pressures up to 60 psig / 4.14 bar</li> <li>• Stainless steel piercing tip</li> <li>• Reduced decaying inlet characteristic</li> <li>• Integrated relief valve</li> <li>• Adjusting knob with locking-nut</li> </ul>	3000 psig / 206.84 bar	Cv: 0.025	SAE 360 Brass  6061-T6 Aluminum, Clear Anodized
<b>2310N SERIES</b> 	<ul style="list-style-type: none"> <li>• Single stage</li> <li>• Neoprene diaphragm</li> <li>• PFA Teflon® seat</li> <li>• Reduced decaying inlet characteristic</li> <li>• Adjusting knob with locking-nut</li> </ul>	3000 psig / 206.8 bar	Cv: 0.025	6061-T6 Aluminum, Clear Anodized
<b>2300S SERIES</b> 	<ul style="list-style-type: none"> <li>• Single stage</li> <li>• Elastomer free</li> <li>• Elgiloy® diaphragm</li> <li>• PTFE seat</li> <li>• Outlet pressures up to 150 psig /10.34 bar</li> </ul>	3000 psig / 206.84 bar	Cv: 0.05	SAE 360 Brass, Nickel Plated  6061-T6 Aluminum, Nickel Plated  316 Stainless Steel  303 Stainless Steel

*Viton® and Teflon® are registered trademarks of E.I.dePont de Nemours and Company*

## TRANSPORTABLE. PRESSURE REDUCING REGULATORS.

SERIES	FEATURES	MAX INLET PRESSURE	FLOW CAPACITY	BODY MATERIAL
<b>2300C SERIES</b> 	<ul style="list-style-type: none"> <li>Designed for use w/ disposable gas cartridges</li> <li>Robust stainless steel piercing tip</li> <li>Integrated relief valve</li> <li>Adjusting knob w/ locking nut</li> </ul>	3500 psig / 241.3 bar	Cv: 0.04	SAE 360 Brass 6061-T6 Aluminum, Clear Anodized
<b>2700 SERIES</b> 	<ul style="list-style-type: none"> <li>Piston sensed</li> <li>Teflon® seat</li> <li>Outlet pressures up to 60 psig / 4.14 bar</li> <li>Factory preset flow settings from 0.25 liters/min to 9.0 liters/min</li> <li>Wide variety of shut off valve options</li> </ul>	3000 psig / 206.84 bar	preset: 0.25 lpm - 9.0 lpm	SAE 360 Brass SAE 360 Brass, Nickel Plated 6061-T6 Aluminum, Clear Anodized 316 Stainless Steel 303 Stainless Steel
<b>2701 SERIES</b> 	<ul style="list-style-type: none"> <li>Piston sensed</li> <li>PTFE seat</li> <li>Standard preset control pressure: 40-80 psig (2.76 - 5.52 bar)</li> <li>Factory preset flow from 0.1 to 4.0 liters/min</li> <li>Wide variety of shut off valve options</li> </ul>	3000 psig / 206.84 bar	preset: 0.1 slpm - 4.0 slpm	SAE 360 Brass SAE 360 Brass, Nickel Plated 6061-T6 Aluminum, Clear Anodized 316 Stainless Steel 303 Stainless Steel
<b>2780 SERIES</b> 	<ul style="list-style-type: none"> <li>Piston sensed</li> <li>Compact and light-weight</li> <li>Teflon® seat</li> <li>Outlet pressures up to 60 psig / 4.14 bar</li> <li>Factory preset flow settings from 0.25 liters/min to 7.0 liters/min</li> </ul>	1000 psig / 68.95 bar	preset: 0.25 lpm - 7.0 lpm	SAE 360 Brass SAE 360 Brass, Nickel Plated 6061-T6 Aluminum, Clear Anodized 303 Stainless Steel

Teflon® is a registered trademark of E.I.dePont de Nemours and Company,

## TRANSPORTABLE. PRESSURE REDUCING REGULATORS.

SERIES	FEATURES	MAX INLET PRESSURE	FLOW CAPACITY	BODY MATERIAL
<b>2900 SERIES</b> 	<ul style="list-style-type: none"> <li>Adjustable Click stop, 12 position, variable flow settings from 0 to 8.0 lpm</li> <li>Teflon® seat</li> <li>Standard preset control pressure 15 psig / 1.03 bar</li> <li>Integral relief valve</li> <li>Optional two-stage design</li> </ul>	3500 psig / 241.3 bar	0.3, 0.5, 1.0, 1.5, 2.0, 2.5, 3.0, 5.0, 6.0, 7.0, 8.0 SLPM	6061-T6 Aluminum, Clear Anodized
<b>4300N SERIES</b> 	<ul style="list-style-type: none"> <li><b>Two stage regulator</b></li> <li>1st stage piston, 2nd stage neoprene or viton® diaphragm</li> <li>Teflon® &amp; neoprene seats</li> <li>Outlet pressures up to 100 PSIG / 6.89 bar</li> <li>Precise stable delivery pressure even as the supply pressure decreases</li> <li>Low internal volume</li> </ul>	3000 psig / 206.84 bar	Cv: 0.04	6061-T6 Aluminum, Clear Anodized  303 Stainless Steel
<b>4300S SERIES</b> 	<ul style="list-style-type: none"> <li><b>Two stage regulator</b></li> <li>1st stage piston, 2nd stage Elgiloy® diaphragm</li> <li>Teflon® seats</li> <li>Outlet pressures up to 100 PSIG / 6.89 bar</li> <li>Precise stable delivery pressure even as the supply pressure decreases</li> <li>Low internal volume</li> </ul>	3000 psig / 206.84 bar	Cv: 0.04	SAE 360 Brass, Nickel Plated  6061-T6 Aluminum, Clear Anodized  303 Stainless Steel  316 Stainless Steel  Monel®
<b>4700 SERIES</b> 	<ul style="list-style-type: none"> <li><b>Two stage design</b> for stable delivery pressures</li> <li>40 micron integral inlet filter</li> <li>Preset, fixed flow</li> <li>Piston sensed</li> <li>Teflon® seat</li> </ul>	3000 psig / 206.84 bar	preset: 0.25 lpm - 9.0 lpm	SAE 360 Brass  SAE 360 Brass, Nickel Plated  6061-T6 Aluminum, Clear Anodized  303 Stainless Steel

Teflon® and Viton® are registered trademarks of E.I. de Pont de Nemours and Company,  
Elgiloy® is a registered trademark of Elgiloy Specialty Metals Division, Combined Metals of Chicago L.L.C.